



(<https://www2.avanttecono.com/global>)



SPECIFICATIONS - AVANT 750



LIFT CAPACITY

1400
kg



ENGINE POWER

49
hp diesel



LIFT HEIGHT

3
m



SPEED

24
km/h

By continuing to use the site, you agree to the use of cookies.



Read more (<https://www2.avanttecono.com/global/cookie-policy>)

SPECIFICATIONS

Length	3060 mm
Width	see table
Height	2100 mm
Weight, starting from	1910 kg
Standard wheels	320/55-15" TR/grass
Transmission, drive	hydrostatic
Aux. hydraulics oil flow / pressure	70 l/min @ 225 bar
Turning radius inside/outside	1240 / 2780 mm
Max. lifting height	3080 mm
Max. lifting capacity (hydr.)	2100 kg
Tipping load *	1400 kg
Max. breakout force / 50 cm	1700 kg
Engine make and type	Kubota V2403
Engine output (ISO Gross)	36 kW (49 hp)
Fuel	Diesel

*) Load is measured at 400 mm from the attachment coupling plate, including attachment weight (70 kg) and with counterweights.

PULLING FORCE

Wheel size	Drive speed	Pulling force
320/60-12 HD	20 km/h	1880 kp
320/55-15	23 km/h	1750 kp
400/50-15	24 km/h	1600 kp

WIDTH

Wheel size	Width
27 x 8.50 - 15	1080 mm
26 x 12.00 - 12	1350 mm
320/60-12 HD	1350 mm
320/55-15	1360 mm
400/50-15	1450 mm

HEIGHT WITH CAB

	26x12.00-12 or 320/60-12 wheels	320/55-15 wheels	400/50-15 wheels
LX Cab	2078 mm	2112 mm	2132 mm
DLX Cab	2105 mm	2139 mm	2169 mm
DLX with A/C	2241 mm	2275 mm	2305 mm
the roof			

By continuing to use the site, you agree to the use of cookies.



Read more (<https://www2.avanttecono.com/global/cookie-policy>)

DIMENSIONS



By continuing to use the site, you agree to the use of cookies.



Read more (<https://www2.avantteco.com/global/cookie-policy>)