



# PULVERIZER

**TOP QUALITY  
AVAILABLE  
FROM STOCK**

- » • Fast open/close cycle
- High closing force
- Equipped with cutting blade
- Equipped with rechargeable toothplate
- Available with or without rotation



**3 years  
warranty**



## *Pladdet*



**Pladdet bv**

Paulinaweg 6-10  
4521 RE Biervliet  
The Netherlands

Tel. 0031 115 - 48 13 51

Fax 0031 115 - 48 20 54

Mail: [info@pladdet.nl](mailto:info@pladdet.nl)

Website: [www.pladdet.biz](http://www.pladdet.biz)

[www.pladdet.biz](http://www.pladdet.biz)

# Hydraulic Pulverizer



The pulverizer is designed for demolition of concrete structures and buildings, the rapid removal of concrete and reinforced cutting steels and profiles. The pulverizer has 1 cylinder which is equipped with a protective cover so there is less change on damage. The Pladdet pulverizer is made of Hardox and the movable jaw of reinforced durable cast iron. Delivers maximum performance with a minimum of wear.

TYPE		PDP05	PDP10	PDRP10	PDP15	PDRP15	PDP20	PDRP20	PDP25	PDP30	PDRP30	PDP45	PDRP45
Working weight	Kg	250	620	800	950	1150	1500	1850	1950	2750	2650	3850	4600
Machine class	Ton	2 - 5	7 - 12	7 - 12	12 - 17	12 - 20	18 - 22	20 - 30	20 - 26	25 - 35	25 - 35	35 - 48	38 - 48
Closing force blades	Ton	37	87	87	163	163	191	186	258	257	288	366	350
Closing force middle tooth	Ton	17	34	34	67	67	91	84	116	121	132	180	156
Closing force front tooth	Ton	11	21	24	42	42	60	54	86	79	99	117	115
Max. spread	Mm	440	700	620	790	790	850	920	950	1100	1105	1290	1290
Required oil flow	Ltr/min	45	80	80	160	160	280	280	240	280	235 - 380	380	280 - 380
Max. operating pressure	Bar	250	250	250	320	320	320	320	320	320	320	320	320
Height	Mm	1020	1380	1620	1650	1850	1830	2090	1960	2200	2570	2450	3040
Length of cutting blade	Mm	75	102	102	140	140	150	150	200	200	200	250	-
Cycle times (O/C)	Sec	1.3 / 1.3	2.0 / 2.6	2.0 / 2.6	2.1 / 1.9	1.9 / 1.8	2.9 / 3.0	2.9 / 3.0	2.5 / 2.2	2.4 / 3.1	2.8 / 2.2	3.7 / 3.2	-