



RM80 GO! – impact crusher with crawler gear

Throughput	Up to 160 t/h, depending on material
Feed size	Edge length max. 650 mm
Inlet opening	860 x 650 mm
Crusher unit	RUBBLE MASTER HMH impact crusher with 2 or 4 hammers
Operation	One operator using radio control for crushing and manoeuvring operations
Feed unit	Asymmetric 2,6 m ³ vibro-channel with two 3.1 kW vibrator motors Effective feed length and width: 2,980 x 1,990 mm Feed Control System for automatic conveying in line with crusher load Wear-resistant Hardox 400 cladding
Pre-screening	Efficient pre-screening using bar mesh screen Screen area 1,050 x 800 mm Output on main discharge conveyor via fully integrated bypass chute
Discharge belt crushed material	Folding conveyor 800 mm wide, folds into transport position hydraulically Discharge height 2,950 mm
Drive unit	John Deere Diesel engine, 6 cylinder 168 kW bei 1,800 rpm EU-RL2004/26 certified Synchronous generator 40 kVA 400 V 230 V and 400 V outlets for external drives up to 15 kVA
Release System	Removes blockages inside crusher
Magnetic separator	Extra strong magnet with left/right function, belt width 800 mm
Transport system	Crawler gear
Weight	23,600 kg
Options	Dust suppression using water spray inside crusher and at outlet Filling pump Discharge belt pre-screened material Hammer changing system Cable remote control Central lubrication system Blind plate

Specifications subject to change in line with technical developments.
This machine complies with Directive 2006/42/EC of the European Parliament.

COMPACT RECYCLING FOR WINNERS

RUBBLE MASTER[®]
COMPACT RECYCLER

RUBBLE MASTER HMH GmbH
Im Südpark 196 - AT 4030 Linz – Austria
T +43 (0) 732 737117-360
F +43 (0) 732 737117-101
sales@rubblemaster.com